## EWPi 9471

## Built-in multi-temperature wine fridge







dity Fresl

UV Protect Plus

Vibrate Safe

ate Inf

nity Sof ht Sys

Soft System Telescopic II Rails S Touch & Swipe Display





 $^1$  These models are only bound for storing wine. Maximum DIN norm bordeaux bottles capacity (0.75 l) as per norm NF H 35-124 (H: 300.5 mm, Ø 76.1 mm)

sump. in 365 days/24 h  Bordeaux bottles 0.75 Ltr  75¹  ne  232 l²  ut  36 dB(A)  ing  SN-ST (+10 °C to +38 °C)  Isolierglastür / Stahl  mensions in cm (h / w / d)  213.4 / 45.7 / min. 63.5  ntrol  3.5" LCD colour display, behind the door, touch- & swipe  Digital temperature display for both wine zones  se of malfunction  visual and acoustic  re zones  re zones  2  re range  +5 °C to +20 °C  cooling circuits	Туре	Fixed door / Built-in appliance for integrated use
Bordeaux bottles 0.75 Ltr  Te  232 l²  tt  36 dB(A)  ing  SN-ST (+10 °C to +38 °C)  Isolierglastür / Stahl mensions in cm (h / w / d)  213.4 / 45.7 / min. 63.5  htrol  3.5" LCD colour display, behind the door, touch- & swipe Digital temperature display for both wine zones se of malfunction  visual and acoustic  acoustic  re zones  2  re range  +5 °C to +20 °C  cooling circuits	Energy efficiency class	GA
te to the second	Energy consump. in 365 days/24 h	154 kWh
tet 36 dB(A) ing SN-ST (+10 °C to +38 °C) Isolierglastür / Stahl mensions in cm (h / w / d) 213.4 / 45.7 / min. 63.5 introl 3.5" LCD colour display, behind the door, touch- & swipe Digital temperature display for both wine zones se of malfunction visual and acoustic acoustic re zones 2 re range +5 °C to +20 °C cooling circuits 1	Max. No. of Bordeaux bottles 0.75 Ltr	75¹
ing SN-ST (+10 °C to +38 °C)  Isolierglastür / Stahl mensions in cm (h / w / d)  213.4 / 45.7 / min. 63.5  htrol  3.5" LCD colour display, behind the door, touch- & swipe Digital temperature display for both wine zones se of malfunction  visual and acoustic  acoustic  re zones  2 re range  +5 °C to +20 °C cooling circuits	Total volume	232 l²
Isolierglastür / Stahl mensions in cm (h / w / d)  213.4 / 45.7 / min. 63.5  Introl  3.5" LCD colour display, behind the door, touch- & swipe Digital temperature display for both wine zones se of malfunction  visual and acoustic  acoustic  re zones  2 re range  +5 °C to +20 °C cooling circuits  1	Noise output	36 dB(A)
mensions in cm (h / w / d)  213.4 / 45.7 / min. 63.5  htrol  3.5" LCD colour display, behind the door, touch- & swipe Digital temperature display for both wine zones se of malfunction  visual and acoustic  acoustic  re zones  2 re range  +5 °C to +20 °C cooling circuits	Climate rating	SN-ST (+10 °C to +38 °C)
ntrol 3.5" LCD colour display, behind the door, touch- & swipe Digital temperature display for both wine zones se of malfunction visual and acoustic acoustic re zones 2 re range +5 °C to +20 °C cooling circuits 1	Door	Isolierglastür / Stahl
Digital temperature display for both wine zones se of malfunction visual and acoustic acoustic  re zones 2 re range +5 °C to +20 °C cooling circuits 1	Aperture dimensions in cm (h / w / d)	213.4 / 45.7 / min. 63.5
Digital temperature display for both wine zones se of malfunction visual and acoustic acoustic  re zones 2 re range +5 °C to +20 °C cooling circuits 1	Controls	
re zones 2 re range +5 °C to +20 °C cooling circuits 1  visual and acoustic	Type of Control	3.5" LCD colour display, behind the door, touch- & swipe
re zones 2 re range +5 °C to +20 °C cooling circuits 1		Digital temperature display for both wine zones
re zones 2 re range +5 °C to +20 °C cooling circuits 1	Alarm in case of malfunction	visual and acoustic
re range +5 °C to +20 °C cooling circuits 1	Door alarm	acoustic
re range +5 °C to +20 °C cooling circuits 1	Features	
cooling circuits 1	Temperature zones	2
	Temperature range	+5 °C to +20 °C
system Convection cooling, fresh air supply via FreshAir activated	Adjustable cooling circuits	1
	Forced air system	Convection cooling, fresh air supply via FreshAir activated
charcoal filter		charcoal filter
nt InfinityLight	Interior light	InfinityLight
rial Beech wood fittings	Shelf material	Beech wood fittings
elves 9	Storage shelves	9
elves on telescopic rails 9	Pull-out shelves on telescopic rails	9
s Reversible door hinge, left	Door hinges	Reversible door hinge, left
9005382266878	EAN-Nr.	9005382266878



 $<sup>^{2}</sup>$  In accordance with Regulation EU 2019/2016 we indicate the total volume to the nearest integer (rounded off) and the volume of the frozen compartments and refrigeration compartments to one place after the decimal point.