

LIEBHERR

ICBNd 5173 Fridge-Freezer


Fully Integrated

DIMENSIONS

H: 177.2 - 178.8 cm W: 56 - 57 cm D: 55.0 cm

VOLUME

Volume total 243 | Refrigerator compartments 173 | of which BioFresh 68.1 | Freezer compartments 71 | Of which 4-star compartment 70.9 |



MANAGEMENT AND FUNCTIONS

Control: 2,4" TFT colour display, Touch &

Swipe display

Control unit: Touch & Swipe Number of temperature zones: 3

Number of regulated refrigeration circuits: 2

Temperature display: Fridge, freezing compartment& BioFresh safe

Connectivity solution: retrofittable

Adjustable on appliance and via app: SuperCool, SuperFrost, Door

alarm - cooling, Door alarm - freezing Adjustable on app: BottleTimer, NightMode Adjustable on appliance: Display lock

POWER AND CONSUMPTION

Energy efficiency class D

Energy consumption in 24h 0.569 kWh / 24h Energy consumption per year 208 kWh/a

Climate class: SN-ST Noise level: 34 dB Sound emission class: B Voltage: 220-240 V ~ Frequency: 50-60 Hz

Connection rating: 1.4 A 183 W

REFRIGERATOR COMPARTMENT

Adjustable temperature range: +3 $^{\circ}\text{C}$ to +9 $^{\circ}\text{C}$

Moisture regulation: DuoCooling

Refrigerator compartment climate zones

- · BioFresh with HydroBreeze
- · Fish & Seafood safe
- · Fruit & Vegetable safe
- · Meat & Dairy safe

Freshness technology: BioFreshProfessional

Number of BioFresh safes: 2

FINISH White

Despite careful data management, our brands reserve the right to make changes, and discrepancies may occur.



Head Office / Showroom Dubai PO Box 37959, Dubai +971 4 380 9490 Showroom Abu Dhabi PO Box 28239, Abu Dhabi +971 2 444 6160 Service Center UAE 600 555 602



LIEBHERR

ICBNd 5173 Fridge-Freezer

Fully Integrated

Interior light of BioFresh safe: LED light

extendible on telescopic rails

Variable uses as Fruit & Vegetable safe or Meat & Dairy safe: 1

Defrosting method: Automatic

Forced air cooling FreshAir filter: in valve

Pull-out system drawer: Fully-extendible telescopic rails with self-

closing mechanism and soft stop mechanism

SoftSystem

Number of storage shelves: 4

Of which separable: 1

of which height-adjustable: 3 Bottle storage: Integrated

Bottle rack: 1

Number of can racks: 1 VarioBox: Pull-out VarioBoxes: 2 Butter dish Egg tray: Variable

Number of FlexSystems: 1 Storage rack: Bottle and can rack

Height-adjustable inner door shelf: Gradual adjustment

INSTALLATION

Door assembly: Fixed door

Max. kitchen unit door weight: 18/12

Door hinges: Right reversible

Door hinge replacement: Possible for customer

Door opening angle: 115° Door seal: Replaceable Height-adjustable feet: 2

Levelling bars

Number of levelling bars: 2

Ventilation grates

FREEZER COMPARTMENT

Temperature range: -15 °C to -26 °C Cooling technology: NoFrost

Freezer compartment position: Bottom

Defrosting method: Automatic

Storage time in case of fault according to GS: 9 h

Freezing capacity in 24 hours according to GS: $6\ kg$ / 24h

No. of drawers in freezer compartment: 3

FrostSafe: Drawers closed on all sides with transparent front Drawer pull-out system:Partially-extendible telescopic rails

Interior light: LED light

VarioSpace IceMaker

Type of hose: Mains water hose with WaterStop

IceMaker safe lighting

Water inlet: Fixed water connection lce cube production: 1.2 kg / 24h

Ice cube storage: 5 kg

Number of cold storage accumulators: 2

Freezer tray: 1 Star-rating: 4

DESIGN AND MATERIALS

Dry rear panel

Material dry back wall: Stainless steel with SmartSteel

Inner door décor: SmartSteel

Design of inner door rack: Premium GlassLine
Material door shelves: Glass with stainless steel trim
Storage shelf material, refrigerator compartment: Glass

Material of adjustable shelves in the freezer compartment: Glass

Door material: Steel



Despite careful data management, our brands reserve the right to make changes, and discrepancies may occur.



Head Office / Showroom Dubai PO Box 37959, Dubai +971 4 380 9490 Showroom Abu Dhabi PO Box 28239, Abu Dhabi +971 2 444 6160 Service Center UAE 600 555 602

